


LISY - DVOŘÁK
wood gluing presses



D-SLS

GLUE LAMINATED TIMBER PRESS



TECHNICAL PARAMETERS	D-SLS	
overall machine length	according the working length	m
overall machine height	2 200	mm
overall depth (width)	810	mm
weight	according the length	kg
max. gluing length (X axis)	3 4 5 6	m
max. gluing height (Y axis)	1 450	mm
max. material thickness = gluing depth (Z axis)	90	mm
pressure	individual	kg/cm ²
number of pressing units	6 - 18	pcs
number of front aligning beams	4 - 12	pcs
max. pressing unit force	2 000 [20]	kg [kN]
max. front aligning bar force (manual - screw)	300 [0,3]	kg [kN]
pressing unit stroke	90	mm
front aligning beam stroke	90	mm
electrohydraulic pump power	1,5 - 2,2	kW
pressure setting	on control panel	-
electrical protection	IP 54	-
voltage	3x 400V / 50 Hz	-
hydraulic oil class	HM 46	12 liters

* machine equipment can be modified by client requirements individually

LISY - DVOŘÁK, s.r.o.

Kňovická 344

264 01 Sedlčany, Czech Republic

e-mail: info@lisy-dvorak.cz

web: www.lisy-dvorak.cz

GSM: **00420 732 240 341**

GSM: **00420 736 645 159**



<https://www.instagram.com/lisydvorak/>



<https://www.facebook.com/lisydvorak/>



<https://www.youtube.com/channel/UCz8HvcZz27siCo0CnglizOQ>